

300 SERIES



SPECIFICATIONS	300M1-A1
TYPE OF VEHICLE	Extra Heavy Duty (ex. Ford F-550)
RECOMMENDED MAX GVW	30,000 lbs GVW
RECOMMENDED MAX SPEED	40 mph
FRAME CONSTRUCTION	Steel
STEERING ASSIST UPGRADE (adds 25 lbs)	Yes
ASSEMBLY WEIGHT	810 lbs
INTERNAL SUSPENSION	Concentric Pivot with Independent Offset Rocker Arm
TRACK TREAD WIDTH	20"
TRACK TREAD STYLE	All-Terrain, Self-Cleaning
TRACK MATERIAL	Rubber w/ Internal Composite Rods/Cord
RECOMMENDED OPERATING TEMP	(Ambient) -40° to +130°
AXLE HEIGHT	25.5"
GROUND CONTACT LENGTH	(Hard Surface) 36" / (Soft Surface) 65"
GROUND CONTACT SURFACE AREA	710 sq in min / 1,300 sq in max
SPROCKET DIAMETER	24"
WHEELS TYPE	(11) 10" x 2.5" - (3) 13" x 2.5"
ROAD WHEEL COUNT	12, 3 rows
WHEEL MATERIAL	Aluminum
PAINT COLOR	Yellow (Standard, other colors available)

* ALL SPECS ARE PER CORNER

MODELS IN SERIES: 200M1-A1, 200M1-A1-SA



FORD F-550 ON 300M1-A1



MATTRACKS
RUBBER TRACK CONVERSIONS

ALL SPECIFICATIONS ARE APPROXIMATE AND WE RESERVE THE RIGHT TO MAKE CHANGES OR MODIFICATIONS WITHOUT NOTIFICATION

202 Cleveland Ave E · PO Box 214 · Karlstad, MN 56732 · 877.436.7800 · mattracks.com