

# zXT SERIES



SPECIFICATIONS	zXT UR	zXT UR HD	XT UR+ / XT UR HD+ (REAR ONLY)
TYPE OF VEHICLE	UTV		
RECOMMENDED MAX GVW	3,500 lbs	4,200 lbs	3,500 / 4,200 lbs
FRAME CONSTRUCTION	Aluminum & Steel		
SPROCKET DRIVE UPGRADE	Yes		
ASSEMBLY WEIGHT	140 lbs	164 lbs	152 / 182 lbs
SUSPENSION	Adjustable Shape Changing Suspension (SCS)		
SUSPENSION LINKS	4		2 or 4
SUSPENSION SPRINGS	Double	Triple	Triple+ or Quad+
TRACK TREAD WIDTH	11"		
TRACK TREAD STYLE	All-Terrain, Self-Cleaning		
RUBBER TRACK CONSTRUCTION	Rods, HD Ply, Std Cord	Rods, HD Ply, HD Cord	
RECOMMENDED OPERATING TEMP	(Ambient) -40° to +130°		
GROUND CONTACT LENGTH	(Hard Surface) 30" / (Soft Surface) 40"		(Hard Surface) 43" / (Soft Surface) 53"
GROUND CONTACT SURFACE AREA	330 sq in min / 440 sq in max		473 sq in min / 583 sq in max
SPROCKET DIAMETER (STANDARD)	14"		
ROAD WHEEL COUNT	8, 2 rows		10, 2 rows
WHEEL MATERIAL	UHMW / Rubber	UHMW / Aluminum / Rubber	UHMW / Rubber or UHMW / Aluminum / Rubber
PAINT COLOR	Natural Aluminum		

\* ALL SPECS ARE PER CORNER EXCEPT GVW

MODELS IN SERIES: zXT UR, zXT UR HD



CAT CUV85 ON zXT UR



TEXTRON PROWLER PRO ON zXT UR



CAT CUV85 ON zXT UR